











The Odyssey 600 is a high-power horticultural LED grow light ideal for mid-height to high-bay farming installations.

Manufactured in the UK using the latest in LED technology and enclosed in a robust linear extrusion this luminaire is IP66 rated and built to last. The accompanying remote PSU can be mounted independently to increase configuration options.

Mounting options include rear mounting brackets or a suspension kit to ensure installation is easy whatever your set-up.



LIGHT OUTPUT

LED Colour	See spectra options			
PPE	up to 3.8 µmol/J			
PPF	up to 1812 µmol/s			
Beam Angle	120°			

ELECTRICAL


Input Voltage	90-305 VAC or 249-528 VAC
Connection type	Trailing Lead
Dimmable	0-10V / Wireless
PF	>0.95 PF

PHYSICAL & ENVIRONMENTAL

Finish	Anodised aluminium
Length options	1056mm
Storage Temp	-30°C to 85°C
Operating Temp	-10°C to 35°C
IP Rating	IP66
Cable Exit/Entry	End
Weight	6.5 kg
Lifetime	L90 >55,000 hrs

Vertically Urban run regular development cycles, continuously optimising and balancing product specifications to best suit our customers. All information therefore, is intended as a guide and specifications may change on occasion without notice or announcement. Technical data is measured under controlled conditions, expected performance is within #1-10% of advertised figures. Information provided is intended as a description of the product and shall go the useful in the form of any contract.










ODYSSEY 600






SPECTRA OPTIONS








SPECTRUM PHOTON DISTRIBUTION

OD01	11%	0%	89%	0%
OD02	17%	8%	75%	0%
OD03	10%	25%	64%	1%

LIGHT DISTRIBUTION



DIMENSIONS





SPECIFICATIONS

Part No.	Product Code	Volta (VAC		Power (W)	*PPF (µmol/s)	†PPE (µmol/J)	
016802	VU-ODYSSEY-600-OD01-1056mm-230V-IP66	230	OD01	549	1812	3.3	
016814	VU-ODYSSEY-600-OD01-1056mm-400V-IP66	400	OD01	549	1812	3.3	
016817	VU-ODYSSEY-600-OD02-1056mm-230V-IP66	230	OD02	523	1568	3.0	
016818	VU-ODYSSEY-600-OD02-1056mm-400V-IP66	400	OD02	523	1568	3.0	
016804	VU-ODYSSEY-600-OD03-1056mm-230V-IP66	230	OD03	521	1459	2.8	
016816	VU-ODYSSEY-600-OD03-1056mm-400V-IP66	400	OD03	521	1459	2.8	


 $^{\dagger}\!A$ 3.8µmol/J full red luminaire is available upon request $$^*\!Typical$ PPF +/-10%

ACCESSORIES

Part No.	Product Code
016856	vu-mounting-kit-odyssey-unistrut
016857	vu-mounting-kit-odyssey-universal-cable

Each Odyssey luminaire is supplied with a power supply as standard. A separate hanging kit of the desired type should be ordered for each lumnaire.













LIGHTING THE FARMS OF THE FUTURE



CONTACT DETAILS

VERTICALLY URBAN

Typhoon House Moxon Way Leeds West Yorkshire LS25 6FB United Kingdom



hello@verticallyurban.com



+44(0)113 322 6459



vertically urban com

