

hello@verticallyurban.com VERTICALLY URBAN | Typhoon House, Moxon Way, Leeds, West Yorkshire, LS25 6FB, United Kingdom





Enhance your horticultural operation with Odyssey Tunable, a luminaire that seamlessly combines the adaptability of advanced LED technology with the power of the 'high-bay' top light form factor. Crafted in the UK using cutting-edge tunable spectrum LED technology, Odyssey Tunable offers unparalleled versatility in greenhouse environments of any scale with its two varients: the powerful 600 model, and the more compact 300.

Enhance your crop's growth journey with the dynamic precision of Odyssey Tunable's four individual control channels. Effortlessly manipulate the output spectrum to cater to your crops' distinct requirements and maximize energy efficiency across each growth stage. Whether you're aiming to emulate sunrise or synchronize lighting regimes with your crops' circadian rhythm, Odyssey Tunable empowers you to turn possibilities into reality.

Designed for durability, Odyssey Tunable boasts an IP66 rating, guaranteeing longevity even in demanding agricultural settings. The included remote PSU offers flexible mounting options, allowing for easy integration into any setup.



# LIGHT OUTPUT

LED Colour		Blue, White, Red, Far Red
Controllable Channels		4
PPE		>3.0 µmol/J
PPF	300	up to 784 µmol/s
rrr	600	up to 1568 µmol/s
Beam Angle		120°

# **ELECTRICAL**


Input Voltage	90-305 VAC
Control Protocol	Modbus RTU or DMX
Connection type	Trailing Lead
Dimming Range	0-100% (Each Channel)
PF	>0.9

# **PHYSICAL & ENVIRONMENTAL**

Finish	Anodised aluminium
Storage Temp	-30°C to 85°C
Operating Temp	-10°C to 35°C
IP Rating	IP66
Cable Exit/Entry	End
Lifetime	Q90 >55,000 hrs
Length options 306	
Weight 30	· •



Vertically Urban run regular development cycles, continuously optimising and balancing product specifications to best suit our customers. All information therefore, is intended as a guide and specifications machange on occasion without notice or announcement. Technical data is measured under controlled conditions, expected performance is within +/- 10% of advertised figures. Information provided is intended as a description of the performance and figure in the performance is within +/- 10% of advertised figures. Information provided is intended as a description of the performance is within +/- 10% of advertised figures. Information provided is intended as a provided performance is within +/- 10% of advertised figures. Information provided is intended as a guide and specifications may be advertised for the performance of the performance is within +/- 10% of advertised figures. Information provided is intended as a guide and specification in the performance is within +/- 10% of advertised figures. Information provided is intended as a guide and specification in the performance is within +/- 10% of advertised figures. Information provided is intended as a performance is within +/- 10% of advertised figures. Information provided is intended as a guide and specification in the performance is within +/- 10% of advertised figures. Information provided is intended as a guide and specification in the performance is a specific for the performance in the performance is a guide and specific figures.










# **ODYSSEY TUNABLE**





### **TUNABLE SPECTRUM**




Example spectrum when all four channels are set to 100%. Any desired

#### **SPECTRUM PHOTON DISTRIBUTION & RATIOS**

		Green PF		Far Red PF		B:G	R:B	R:FR
ODT01	5%	8%	78%	9%	X	0.6	15.6	8.7
							^All	channels at 100%

#### LIGHT DISTRIBUTION




# **SPECIFICATIONS**

Part No.	Product Code	Spectrum	Power (W)	*PPF (µmol/s)	†PPE (μmol/J)
021428	VU-ODYSSEY-300-ODT01-532mm-230V-IP66-DMX	ODT01	270	784	>3.0
021387	VU-ODYSSEY-300-ODT01-532mm-230V-IP66	ODT01	270	784	>3.0
021429	VU-ODYSSEY-600-ODT01-1056mm-230V-IP66-DMX	ODT01	540	1568	>3.0
020285	VU-ODYSSEY-600-ODT01-1056mm-230V-IP66	ODT01	540	1568	>3.0

\*Typical PPF +/-10% (all channels at 100%) †Actual luminaire efficacy will vary with luminaire output spectrum settings.

# **DIMENSIONS**




## **ACCESSORIES**

Part No. **Product Code** 

VU-MOUNTING-KIT-ODYSSEY-UNISTRUT 016856 016857 VU-MOUNTING-KIT-ODYSSEY-UNIVERSAL-CABLE

Each Odyssey luminaire is supplied with a power supply and driver kit as standard. A separate hanging kit of the desired type should be ordered for each lumnaire.












LIGHTING THE FARMS OF THE FUTURE



# **CONTACT DETAILS**

# VERTICALLY URBAN

Typhoon House Moxon Way Leeds West Yorkshire LS25 6FB United Kingdom



hello@verticallyurban.com



+44(0)113 322 6459



verticallyurhan.com

